

M-FLEX POWER & GROUND BLOCK

M-Flex Power & Ground Block is wiring tool for collecting up to 24 power or ground conductors into a watertight terminal block. The M-Flex Ground Block is designed for severe duty, outdoor mobile applications and built to withstand the harsh temperatures, shock and vibration, moisture and electrical transients that are common to these environments.



M-Flex
 CONTROLLERS

IP67

 12V
24V

 RoHS
Compliant


FEATURES



Fully encapsulated electronics for complete environmental protection.



Operating temperature
-40°C to +85°C.

Operating Humidity -40°C
to +85°C.



Deutsch DT style connectors.

SPECIFICATIONS

Specifications subject to change without notice. \ Revised 11.25

Supply Voltage	All
Max Current	120A Max – 13 amps per terminal
Connectors	Deutsch DT15-12PA and DT15-12PB
Terminals	2 M8 terminals
Mounting	M4 or #8
Ingress Protection	IP67
Operating Temperature	-40° to 85°C (-40° to 185°F)
Storage Temperature	-40° to 85°C (-40° to 185°F)
Weight	4.8 oz (136.07 g)
Enclosure	3.3 in L x 2.6 in W x 1.6 in H (102 mm L x 78 mm B x 41 mm H)

DIMENSIONS

