

LEGEND SERIES 6PB KEYPAD

The M-Flex Legend Series Keypads have relegendable keycaps and are designed for severe duty, outdoor mobile applications and built to withstand the harsh temperatures, shock and vibration, moisture and electrical transients that are common to these environments.



M-Flex
KEYPADS



FEATURES



Relegendable keycaps.
Standard and custom icons.




Tactile Buttons with actuation feedback.



CAN protocol J1939,
CANopen, NMEA 2000.



Four RGB LED indicators for
brighter illumination and full
color control.



Vertical or horizontal mount.



On/off, momentary, toggle scroll/
step functions for each key.



Deutsch DT style connectors.



Compatible with Marlin Digital
Switchers and IO Controllers.



Optional Bluetooth connectivity.

SPECIFICATIONS

Specifications subject to change without notice. \ Revised 07.23

Supply Voltage	9 – 32VDC.
Max Current	1A @ 12VDC.
CAN Protocol	J1939, CANopen, NMEA 2000.
Baud Rate	250, 500, 1000 kbps.
Switch Backlighting	Dimmable color LED backlighting on switches; intensity controlled via CAN message.
Actuation	Snap dome contacts operate at 340 grams of force.
Connector	Deutsch DT04-4P.
Mounting	(2) M6 x 1.00 (25.40mm) stud; 35 in. lbs torque.
Ingress Protection	IP67.
Operating Temperature	-40° to 85°C (-40° to 185°F).
Storage Temperature	-40° to 85°C (-40° to 185°F).
Enclosure	PC PBT alloy plastic resin.

DIMENSIONS

