

LEGEND SERIES 12PB KEYPAD

The M-Flex Legend Series Keypads have relegendable keycaps and are designed for severe duty, outdoor mobile applications and built to withstand the harsh temperatures, shock and vibration, moisture and electrical transients that are common to these environments.



FEATURES



Relegendable keycaps
Standard and custom icons.




Four RGB LED indicators for
brighter illumination and full
color control.




Deutsch DT style connectors.



Tactile Buttons with actuation
feedback.



Vertical or horizontal mount.



Compatible with Marlin Digital
Switchers and IO Controllers.



CAN protocol J1939,
CANopen, NMEA 2000.



On/off, momentary, toggle scroll/
step functions for each key.




Optional Bluetooth connectivity.

SPECIFICATIONS

Specifications subject to change without notice. \ Revised 07.23

Supply Voltage	9 – 32VDC.
Max Current	1A @ 12VDC.
CAN Protocol	J1939, CANopen, NMEA 2000.
Baud Rate	250, 500, 1000 kbps.
Switch Backlighting	Dimmable color LED backlighting on switches; intensity controlled via CAN message.
Actuation	Snap dome contacts operate at 340 grams of force.
Connector	Deutsch DT04-4P.
Mounting	(2) M6 x 1.00 (25.40mm) stud; 35 in. lbs torque.
Ingress Protection	IP67.
Operating Temperature	-40° to 85°C (-40° to 185°F).
Storage Temperature	-40° to 85°C (-40° to 185°F).
Enclosure	PC PBT alloy plastic resin.

DIMENSIONS



For a detailed specification visit
marlintech.com/m-flex

Marlin Technologies, Inc.
101 Industrial Drive \ P.O. Box 123
Horicon, WI 53032-1803
920.485.4463 \ P
920.485.2899 \ F

MARLINTECH.COM
PROUDLY MADE IN THE USA